

# G-Box Expert GL-4 75W-90


Automotive Gear Oil




Semisynthetic



Mechanical transmissions







Low-temperature properties

**G-Box Expert GL-4 75W-90** is high quality gear oil for heavy duty manual transmissions and rear axles where operations require gear lubricants with excellent load-carrying capability over wide operating temperatures and where extreme pressures are expected. G-Box Expert GL-4 75W-90 is formulated from a blend of synthetic and highly refined mineral base oils and advanced additive package to provide superior wear protection, excellent low temperature characteristics and high temperature stability when compared to conventional mineral gear oils.

## **Applications**

















- Off-highway industries including: construction, quarrying, and agriculture
- Transmissions and axles and other applications where mild extreme pressure gear oil meeting API GL-4 are recommended
- Not suitable for automatic, manual, or semi-automatic transmissions for which engine oil or automatic transmission fluids are recommended
- Not suitable for limited slip applications

Features	Advantages and Potential Benefits	
Good extreme pressure properties	Reduced gear wear and extended life in transmissions	
Excellent frictional properties	Improved smooth shifting performance	
Improved thermal and oxidation stability	Reduced deposits and sludge build-up for long transmission life	
Good low temperature performance	Oil flows and circulates more quickly at low temperatures to extend transmission life	
Rust and corrosion protection	Protection of copper and its alloys for improved gear performance and long component life	
Compatible with all common seal materials	Excellent leakages control	

## Recommendations

**Approvals** 

API GL-4

AVTOVAZ

## **Typical Characteristics**

Properties	Method	G-Box Expert GL-4 75W-90
SAE Viscosity Grade	SAE J306	75W-90
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	111,9
Kinematic Viscosity @100°C, mm²/s	ASTM D445	15,8
Viscosity Index	ASTM D2270	150
Flash Point (COC), °C	ASTM D92	221
Pour Point, °C	ASTM D97	-42
Density @15°C, kg/m <sup>3</sup>	ASTM D4052	856

 **♥** ISO/TS 16949

OHSAS 18001

CERTIFIED

## G-Box Expert GL-4 75W-90 performance benefits



#### Prolonged gear life

Good wear protection – damaged area due to scoring 4.7 times lower (FZG pitting test, C/9/90); Deposits build-up control – oxidation stability 5.2 times better (CEC-L-48-A-00 Apparatus B)

#### Leakage control


Effect on seals materials 2.5 times lower (VDA 675 301 (70 ACM 121433))

## Excellent synchromesh unit performance


Smooth shifting performance – coefficient of friction after 100k gear changes 10% higher (ZF Synchromesh test);

Synchromesh unit wear 6.5 lower (ZF Synchromesh test)

#### Wear protection under high loads\*



#### Synchromesh unit prolonged life\*\*



\*FZG pitting test, C/9/90; \*\*ZF Synchromesh test

#### Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.