

Gazpromneft Compressor Oil

Air compressor oils



Positive/dynamic displacement compressors



Improved thermal stability



Antiwear properties



Corrosion protection



Mineral

Gazpromneft Compressor oils are high quality ashless compressor oils designed for lubrication of positive and dynamic air compressors working in moderate conditions at variable working temperatures. Gazpromneft Compressor oil is formulated with high quality mineral base oils with specially selected additives they are characterized by high resistance to oxidation, excellent anti-corrosion, anti-wear, anti-rust properties. Gazpromneft Compressor oils meet the specification of DIN 51506 VCL.

Applications

- Oil systems of rotary and piston compressors, where oils meeting DIN 51506 VCL/VBL are required
- Rotary screw and rotary vane compressors (Gazpromneft Compressor-46/68)
- Piston compressors (Gazpromneft Compressor-100/150/220/320)
- Centrifugal compressors (Gazpromneft Compressor-46)
- Stationary compressors operating at maximum discharge temperatures of up to 180°C and mobile compressors - of up to 220°C (according to DIN 51506 VCL)

Features	Advantages and Potential Benefits
Low ash and carbon formation	Reduced deposits in discharge lines for improved valve and compressor performance
Excellent thermal stability	Longer oil life for lower maintenance costs
Enhanced wear protection	Less wear resulting in less unexpected downtime
Rust and corrosion protection	Improved protection of valves and reduced wear of rings and cylinders

Approvals

- Rotorcomp Verdichter GmbH (ISO VG 46, 68, 100)
- Ural Compressor Plant (ISO 220)

Meets the requirements

- DIN 51506 VCL
- Ural Compressor Plant
- Sumy Mashine-Building Science and Production Association

Typical Characteristics

Properties	Method	Gazpromneft Compressor Oil					
		46	68	100	150	220	320
ISO Viscosity Grade		46	68	100	150	220	320
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	46	68	100	150	220	320
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	6,7	8,5	11,0	14,7	18,5	23,5
Viscosity Index	ASTM D2270	97	95	93	93	92	91
Autoignition point, °C	ASTM E659	340	374	375	375	376	378
Flash Point (COC), °C	ASTM D92	235	246	257	260	267	271
Pour Point, °C	ASTM D97	-32	-30	-28	-23	-20	-17
Total Acid Number, mg KOH/g	ASTM D664	0,14	0,14	0,14	0,14	0,14	0,14
Density @15°C, kg/m ³	ASTM D4052	879	884	888	892	899	900

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

✔ ISO 9001

✔ ISO 14001

✔ ISO/TS 16949

✔ OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63
www.gazpromneft-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: OilSupport@gazprom-neft.ru 04/2020