

KS-19p A

Air compressor oil

KS-19p A is high quality compressor oil designed for lubrication of reciprocating and rotary piston air compressors working in moderate conditions at variable working temperatures. KS-19p A is formulated with high quality mineral base oils with special additives to provide improved oxidation and thermal stability.

Applications

- Reciprocating and rotary piston compressors working in moderate conditions

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Longer oil life for lower maintenance costs
Wear protection	Less wear resulting in less unexpected downtime
Low evaporation loss	Reducing oil consumption and burn-off to minimize maintenance and oil filling costs

Typical Characteristics

Properties	Method	KS-19p A
ISO Viscosity Grade		220
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	23,2
Viscosity Index	ASTM D2270	88
Flash Point (COC), °C	ASTM D92	272
Pour Point, °C	ASTM D97	-16
Total Acid Number, mg KOH/g	ASTM D664	0,01
Conradson Carbon Residue, wt%	ASTM D189	0,4
Sulphur, wt%	ASTM D6481	0,5
Density @15°C, kg/m ³	ASTM D4052	901

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.