

G-Box Expert GL-5 80W-90

Automotive Gear Oil



Mineral



Drive axles



EP properties



Oxidation Stability



Low-temperature properties

G-Box Expert GL-5 80W-90 is high quality gear oil for heavy duty manual transmissions and rear axles where operations require gear lubricants with excellent load-carrying capability over wide operating temperatures and where extreme pressures and shock loading are expected. G-Box Expert GL-5 80W-90 is formulated from highly refined mineral base oils and advanced additive package to provide excellent wear protection and high temperature stability.

Applications



- Passenger cars, light- and heavy-duty trucks, busses, vans
- Off-highway industries including: construction, quarrying, and agriculture
- Transmissions and axles and other applications where high extreme pressure gear oil meeting API GL-5 are recommended
- Not suitable for automatic, manual, or semi-automatic transmissions for which engine oil or automatic transmission fluids are recommended
- Not suitable for limited slip applications

Features	Advantages and Potential Benefits
Excellent extreme-pressure properties	Increased load-carrying capability for protection against low speed/high torque wear, high speed scoring and spalling
Excellent frictional properties	Improved smooth shifting performance
Improved thermal and oxidation stability	Reduced deposits and sludge build-up for long transmission life
Improved low temperature performance	Oil flows and circulates more quickly at low temperatures to extend transmission life
Rust and corrosion protection	Protection of copper and its alloys for improved gear performance and long component life
Compatible with all common seal materials	Excellent leakages control

Recommendations

- API GL-5

Approvals

- AVTOVAZ

Typical Characteristics

Properties	Method	G-Box Expert GL-5 80W-90
SAE Viscosity Grade	SAE J306	80W-90
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	155,1
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	14,9
Viscosity Index	ASTM D2270	96
Brookfield @-26°C, mPa·s	ASTM D2983	114 000
Flash Point (COC), °C	ASTM D92	220
Pour Point, °C	ASTM D97	-29
Density @15°C, kg/m ³	ASTM D4052	897

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.