

G-Motion 2T

Two-Stroke Engine Oil



Two-stroke engines



High detergent properties



Engine cleanliness



Semisynthetic



Good low temperature performance

G-Motion 2T is high performance low ash oil designed for two-stroke gasoline engines. It is specially designed for land based air-cooled two-stroke engines that are used in motorcycles, chainsaws, lawnmowers and other gardening equipment. G-Motion 2T provides clean engine and environmental performance. It helps to prevent clogging of ports, ring sticking, and spark plug fouling. Mixing with the fuel should be in accordance with the manufacturer's recommendations.

Applications



- High performance land based air-cooled two-stroke engines
- Two-stroke engines where JASO FD (or lower) oils are recommended
- Motorcycles, go-karts, snowmobiles
- Lean oil/fuel ratio chain saws, lawnmowers and other gardening equipment

Features	Advantages and Potential Benefits
Cleaner combustion and reduced deposits in combustion area	Reduces plug fouling and exhaust port deposits help to minimize pre-ignition and extend spark plug and valve life
Smoke-free exhaust	Cleaner environment
High temperature deposits control	Cleaner engines resulting in reduced ring sticking and cylinder scuffing, and extended engine life
Good high and low temperature performance	Wide range of ambient temperature application

Meets the requirements



- JASO FD
- ISO-L-EGD

Recommendations

- API TC

Typical Characteristics

Properties	Method	G-Motion 2T
Color	visually	red
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	9,7
Autoignition temperature	ISO 4589	344
Flash Point (COC), °C	ASTM D92	182
Pour Point, °C	ASTM D97	-38
Density @15°C, kg/m ³	ASTM D4052	869
Sulphated Ash, wt%	ASTM D874	0,15



*JASO M 341; **JASO M 343

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.