

G-Motion 4T 10W-30

Four-Stroke Engine Oil



Small four-stroke engines



Good shear stability



Wide range of operating temperatures



High quality mineral base oils



High oxidation stability

G-Motion 4T 10W-30 is high performance mineral engine oil formulated with modern additives for use in small four stroke engines. It provides complete protection against wear and corrosion at extremely high temperatures, causing viscosity and thermal breakdown of motor oil. G-Motion 4T 10W-30 provides high performance reliability to help protect and clean your engine and help prolong engine life.

Applications



- Small four-stroke gasoline or diesel engines requiring API SG/CD performance (or lower)
- Lawnmowers, generator sets and pumps, brushcutters and other gardening equipment that specify this viscosity grade
- Four stroke outboard/inboard air-cooled engines
- Some smaller four stroke motorcycles
- Not applicable for wet-clutch engines



Features	Advantages and Potential Benefits
Effective wear protection	Extended engine life
High shear stability	Maintains viscosity and stays in grade throughout the oil-change interval
Excellent thermal and oxidation stability	Prolonged oil life allowing extended drain interval protection
Good low temperature performance	Quick cold starting and engine warm-up help to extend engine life

Recommendations

- API SG/CD

Typical Characteristics

Properties	Method	G-Motion 4T 10W-30
SAE Viscosity Grade	SAE J300	10W-30
Kinematic Viscosity @ 40°C, mm ² /s	ASTM D445	77,2
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	11,6
Viscosity Index	ASTM D2270	143
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-38
Density @ 15°C, kg/m ³	ASTM D4052	876
Total Base Number, mg KOH/g	ASTM D2896	6,0



*ASTM D 5293; **Sequence VG

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.