

## Gazpromneft Premium L 10W-40

Passenger Vehicle Engine Oils



Engine oil



Semisynthetic



Engine cleanliness



Gasoline and diesel engines



Multigrade



Advanced polymers

**Gazpromneft Premium L 10W-40** is high quality semi-synthetic engine oil providing excellent high temperature wear protection, cold start performance and inhibits deposit formation. Gazpromneft Premium L 10W-40 is formulated with the use of synthetic technology and advanced additive system to provide improved performance level compared with conventional oils. It provides long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

### Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with API SL, API CF standards
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Broad vehicle application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Excellent low temperature performance	Quick cold weather starting helps to extend engine life
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade

### Specifications

- API SL/CF
- AVTOVAZ

## Typical Characteristics

Properties	Method	Gazpromneft Premium L 10W-40
SAE Viscosity Grade	SAE J300	10W-40
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	97,1
Kinematic Viscosity @100°C, mm <sup>2</sup> /s	ASTM D445	14,3
Viscosity Index	ASTM D2270	151
Flash Point (COC), °C	ASTM D92	232
Pour Point, °C	ASTM D97	-37
Total Base Number, mg KOH/g	ISO 6619	9,0
Density @15°C, kg/m <sup>3</sup>	ASTM D4052	888
Sulfated Ash, wt%	ASTM D874	1,1

## Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.