

LSP 5W30 Syntronic Longlife III

Bardahl LSP 5W30 Syntronic is a fuel-saving, universal engine oil, developed according to the latest techniques, based on specially selected base oils, to which advanced additives have been added to obtain the following properties:

- fuel saving
- reduced formation of combustion residues (low SAPS)
- a smooth cold start
- a safe lubricating film at high operating temperatures
- extended drain intervals
- a very good deterging and dispersing effect
- a very strong anti-wear, anti-corrosion and antifoam power 733321

Application

A universal, fuel-saving, specially formulated engine oil, suitable for petrol, LPG and diesel engines, for which extended drain intervals are possible. This engine oil also contributes to the extension of the service life of particulate filters, due to the low SAPS content. Due to its special composition, this product can be used excellently for the VW 503.01/504.00/507.00 standard.

- **Compatible with 0w30**
LSP 5w30 serves as a replacement for all applications and deployment areas which Bardahl VA 0w30 stood for.
Adaptation to this :
Spec. 506.01 VW v10 5.0 bj 2002-2010 – refresh time limit at 15000km (Subject to change).

Specifications

- API SN
- ACEA C2*/C3
- BMW LONGLIFE-04
- MB 229.31
- MB 229.51
- PORSCHE C30
- VW 503.01
- VW 504.00
- VW 507.00

Analysis data

SAE - class	Test		Average result
	Method	Unit	LSP 5W30
Viscosity; mm ² at 100°C	ASTM D445	mm ² at 100°C	11,40
Viscosity; mm ² at 40°C	ASTM D445	mm ² at 40°C	68,70
Viscosity Index	ASTM D2270		160
Viscosity; m Pa. s at -30 °C	ASTM D5293	mPa.s	6150
Sulphate ash	ASTM D874	Wt%	0.7
Density; , kg/l15 °C	ASTM D4052	g/ml	0,849
tbn	ASTM D2869	mg KOH/g	6,0
pourpoint	ASTM D6892	°C	-39
Flashpoint	ASTM D92	°C	240



Article number 51351

Contents 1 liter

Article number 51355

Contents 5 liter

Article number 51382

Contents 25 liter

Article number 51386

Contents 60 liter

Article number 51392

Contents 210 litres