

# XTC FS 5W30 Synthetic

A modern economical universal engine oil with special base oils give it the natural high viscosity index. With an extensive package of additives, the following properties are achieved:

## Properties

- Saves fuel
- The high viscosity index protects the engine from temperature influences
- Better cold starts
- A safe lubricating film at high operating temperatures
- Good cleaning properties
- Provides high protection against wear, corrosion and antifoam

## Application

A universal engine oil that is suitable for use in all engines, where a 5W30 A1/B1 A5/B5 is prescribed.

## Specifications

- API SL/CF
- ACEA A1/B1-12/A5/B5-16
- FORD WSS-M2C913-C/D
- JAGUAR-LAND ROVER STJLR.03.5003
- RENAULT RN 0700

## Analysis data

Test		Results
SAE - Class	Method	fs 5w30
Density 15 °C	ASTM D4052	g/ml 0,863
Viscosity; m Pa. s at , -30 °C	ASTM D5293	mPa.s 6400
Viscosity; mm <sup>2</sup> /s at 40 °C	ASTM D445	mm <sup>2</sup> /s 67,40
Viscosity; mm <sup>2</sup> /s at 100 °C	ASTM D445	mm <sup>2</sup> /s 10,90
Viscosity index	ASTM D2270	153
Flashpoint COC, °C	ASTM D92	°C 220
Pour point, °C	ASTM D6892	°C -40
Total Base Number	ASTM D2896	mg KOH/g 9,7
Sulfated Ash; wt. %	ASTM D874	wt. % 1,12

**Article number** 50851  
**Contents** 1 liter

**Article number** 50886  
**Contents** 60 litres

**Article number** 50855  
**Contents** 5 liter

**Article number** 50892  
**Contents** 210 litres

**Article number** 50882  
**Contents** 25 litres

