

# LS 5W30 C4 SYNTRONIC

**Bardahl LS 5W30 C4 Syntronic** is a 100% synthetic engine oil that has been specially developed for the aftertreatment systems of Renault engines.

## Application

**Bardahl LS 5W30 C4 Syntronic** is suitable for gasoline and diesel engines of passenger cars with or without turbo that are equipped with a particulate filter (DPF).

## Specifications

- ACEA C3,C4
- FIAT 9.55535-S4
- MB 226.51
- MB 229.31
- MB 229.51
- RENAULT RN 0720

## Analysis of data

Test			Results
SAE class	Method	Unit	LS 5W30 C4 SYNTRONIC
Viscosity; mm <sup>2</sup> at 100°C	ASTM D445	mm <sup>2</sup> /s	11.7
Viscosity; mm <sup>2</sup> at 40°C	ASTM D445	mm <sup>2</sup> /s	68
Viscosity Index	ASTM D2270		169
Viscosity; at -30°C	ASTM D5293	mpa/s	6300
Straight Ash;		wt.%	0.50
Sulfated Ash;	ASTM D874	wt.%	1.09
TBN; mg KOH/g	ASTM D2896	mg KOH/g	7.2
Pourpoint; °C	ASTM D6892	°C	-41
Specific Gravity at 15/15°C	ASTM D4052	g/ml	0.854
Flashpoint; COC; °C	ASTM D92	°C	200

<b>Article number</b>	54151
<b>Contents</b>	1 liters
<b>Article number</b>	54155
<b>Contents</b>	5 liters
<b>Article number</b>	54182
<b>Contents</b>	25 liters
<b>Article number</b>	54186
<b>Contents</b>	60 liters
<b>Article number</b>	54192



Contents

210 liters