



HEXOL SUPERTRUCK 15W40

MOTOR OIL, SUPER HIGH PERFORMANCE DIESEL (SHPD)

PRODUCT DESCRIPTION

Hexol SuperTruck 15W40 is a high quality, multigrade oil, specially formulated for heavy duty diesel applications (trucks, construction, agricultural and lifting equipment), recommended for use in all seasons in naturally aspirated or turbocharged diesel engines not fitted with DPF.

PERFORMANCE FEATURES

- meets the requirements of API CI-4/SL, ACEA E7, ACEA A3/B4;
- meets the specifications of VOLVO VDS-3, RENAULT RLD2, RLD, MAN 3275-1, MAN 3277, MB 228.5, DAF, MACK EO-M plus, CAT ECF-1/2, AVIA DDC 93K215, MIL-L-2104E, JOHN DEERE 6020, 6120, 6220, 6320, 6420, 6420S, Cummins CES 20077/20078, TEDOM 258-3, Tatra TDS 30/16, Global DHD-1, DEUTZ DQC III-10, ZETOR and other types of motor vehicles whose manufacturers recommend an oil with this classification;
- contains anti-wear, anti-corrosion, anti-foaming additives, which prolongs the life of the engine, ensuring optimum lubrication, cooling and protection of the engine operating at very high temperature;
- reduces the oxidation and thinning of the oil at high operating temperatures, ensuring stability, controls deposits and sediments of varnish, rust and carbon.

APPLICATION

- diesel engines that equip cars, vans, heavy machinery, agricultural construction equipment, hydraulic systems, lifting, subjected to heavy exploitation;
- unless otherwise recommended in the machine manual, the maximum interval between two oil changes will be 30.000 Km or a year.

PROPERTIES

Viscosity grade SAE	15W40
API Service	CI-4/SL
Density at 15°C [kg/m ³], max	885
Kinematic Viscosity at 100°C [mm ² /s]	12.5 – 16.3
Viscosity Index, min	135
Flash Point [°C], min	220
Pour Point [°C], max	-33

PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input type="checkbox"/> 4kg	<input type="checkbox"/> 15kg	<input type="checkbox"/> 180kg	<input type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input type="checkbox"/> 208l	<input type="checkbox"/> 1000l
<input type="checkbox"/> 4l	<input checked="" type="checkbox"/> 5l	<input checked="" type="checkbox"/> 10l	<input checked="" type="checkbox"/> 20l	<input checked="" type="checkbox"/> 60l		

HEXOL®

HEXOL LUBE SRL

Zona Metropolitană Oradea • 417166 Paleu, Str. Ardealului nr. 1A, jud. Bihor • România
Telefon +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com