

# TEHNICAL DATA SHEET

# **HEXOL SYNLINE SPRINT 10W40**

MOTOR OIL

# PRODUCT DESCRIPTION

Hexol SYNLINE Sprint 10W40 is a high quality, synthetic blend, multigrade engine oil, recommended for use in all seasons in diesel, gasoline and propane engines. Formulated with highly refined synthetic and mineral base oils and high-performance additives, it meets intensive use requirements, it prevents deposits formation and reduces fuel consumption.

# PERFORMANCE FEATURES

- meets the requirements of API SL/CF, ACEA A3/B4;
- complies with the standards imposed by car manufacturers, such as: specificaţiilor VW 500.00, 501.01, 505.00, MB 229.1, RENAULT 0700, FORD WS-M2, PSA B71 2294, B71 2300, FIAT 9.55535-H2 and many more;
- contains anti-wear, anti-corrosion and anti-foaming additives that prolong the life of the engine;
- ensures lubrication, cooling and protection of the engine operating at very high temperatures;
- controls and minimizes deposits and sediments of varnish, rust and carbon;
- high viscosity and low variation of viscosity influenced by temperature.

## **APPLICATION**

- can be used on all passenger cars and cargo trucks with petrol or gas engines where the manufacturer recommends the use of an SAE viscosity 10W40 and API SL/CF oil;
- unless otherwise stated in the car manual, the interval between two oil changes will be at maximum 15.000 Km, but no more than a year.

### **PROPERTIES**

Viscosity grade SAE	10W40
API Service	SL/CF
Density at 15°C [kg/m³], max	880
Kinematic Viscosity at 100°C [mm²/s]	12.5 - 16.3
Viscosity Index, min	150
Flash Point [°C], min	210
Pour Point [°C], max	-38

#### **PACKAGING**

0.4kg	1kg	4kg	□ 15kg	180kg		
0.231	0.45l	0.51	0.6l	0.91	□ 1	☐ 31
∠ 4I	<b>∑</b> 5I			<b>⊠</b> 60I	<b>∑</b> 208I	X 1000l

HEXOL