

TEHNICAL DATA SHEET

HEXOL SYNLINE SPRINTPLUS 5W30

MOPTOR OIL

PRODUCT DESCRIPTION

Hexol SYNLINE SprintPlus 5W30 is an extra high-performance, fuel saving, synthetic engine oil. It can be used in the latest generation of naturally aspirated or turbocharged, gasoline or diesel engines, ensuring long drain intervals.

PERFORMANCE FEATURES

- meets the requirements of API SN/CF, ACEA A3/B4;
- complies with the standards imposed by renowned car manufacturers, such as: BMW LL-04, VW 502.00, 504.00, 505.00, Porsche C30, MB 229.5, Fiat 9.55535-N2, Renault 0710, PSA B71 2296, JASO DL-1, and others;
- offers excellent reliability at start-up and also at extremely low temperatures;
- increases the engines life, extremely long oil change interval;
- excellent thermal and oxidation stability.

APPLICATION

- suitable for cars, vans and light commercial vehicles, equipped with petrol or diesel engines, supercharged or with natural aspiration, without particle filter, for which the manufacturer recommends an oil with the above mentioned properties;
- the oil replacement interval will be according to the instructions of the engine manufacturer.

PROPERTIES

Viscosity grade SAE	5W30
Density at 15°C [kg/m³], max	870
Kinematic Viscosity at 100°C [mm²/s]	9.3 - 12.5
Viscosity Index, min	160
Flash Point [°C], min	220
Pour Point [°C], max	-40

D	\ \ \	1/ A			
PL	7 (ΚΑ	(- 1	I INI	(–

0.4kg	1kg	4kg		180kg		
0.23l	0.45l	0.5l	0.6l	0.91	□ 1	□ 3I
⋈ 4I		X 10I	× 201	⊠ 60I	X 2081	X 1000l

HEXOL®