

TEHNICAL DATA SHEET

HEXOL SYNLINE SPRINTPLUS 5W40

MOPTOR OIL

PRODUCT DESCRIPTION

Hexol SYNLINE SprintPlus 5W40 is an extra high-performance, fuel saving, synthetic engine oil, ensuring long drain intervals. Recommended for use in the most advanced gasoline or diesel naturally aspirated or turbocharged engines.

PERFORMANCE FEATURES

- meets the requirements of API SN and SM/CF, ACEA A3/B4;
- complies with the standards imposed by renowned car manufacturers, such as: BMW LL-04, VW 502.00, 504.00, 505.00, Porsche C30, MB 229.5, Fiat 9.55535-N2, Renault 0710, PSA B71 2296, JASO DL-1, and others;
- offers excellent reliability at start-up and also at extremely low temperatures;
- increases engine life;
- extremely long oil change interval;
- excellent thermal and oxidation stability;
- the oil retains its properties for 5 years, in the original package tighly closed, away from heat sources and direct sunlight(maximum temperature + 40°C).

APPLICATION

- suitable for cars, vans and light commercial vehicles, equipped with petrol or diesel engines, supercharged or with natural aspiration, without particle filter, for which the manufacturer recommends an oil with the above mentioned properties;
- the oil replacement interval will be according to the instructions of the engine manufacturer.

PROPERTIES

Viscosity grade SAE	5W40
Density at 15°C [kg/m³], max	870
Kinematic Viscosity at 100°C [mm²/s]	12.5 - 16.3
Viscosity Index, min	150
Flash Point [°C], min	225
Pour Point [°C], max	-36

PACKAGING

0.4kg	1kg	4kg	□ 15kg	☐ 180kg		
0.23l	0.45l	0.51	0.6l	0.91	□ 11	3 I
	 51	× 10l	× 20l	⋈ 601	× 2081	X 1000l

HEXOL