

TEHNICAL DATA SHEET

HEXOL SYNLINE SUPERTRUCK 10W40

MOTOR OIL, SUPER HIGH PERFORMANCE DIESEL (SHPD)

PRODUCT DESCRIPTION

Hexol SYNLINE SuperTruck 10W40 is a high quality, multigrade, synthetic blend oil, specially formulated for heavy duty diesel applications (trucks, construction, agricultural and lifting equipment), recommended for use in all seasons, in naturally aspirated or turbocharged diesel engines not fitted with DPF.

PERFORMANCE FEATURES

- meets the requirements of API CI-4/SL, ACEA E7, ACEA A3/B4;
- meets the specification of VOLVO VDS-3, RENAULT RLD2, RLD, MAN 3275-1, MAN 3277, MB 228.5, MACK EO- M plus, CAT ECF-1/2, AVIA DDC 93K215, MIL-L-2104E, JOHN DEERE 6020, 6120, 6220, 6320, 6420, 6420S, Cummins CES 20077/20078, TEDOM 258-3, Tatra TDS 30/16, Global DHD-1, DEUTZ DQC III-10, ZETOR and other types of vehicle whose manufacturers recommend an oil with this classification;
- contains anti-wear, anti-corrosion, anti-foaming additives, which prolongs the life of the engine, ensuring optimum functioning, lubrication, cooling and protection;
- reduces the oxidation and thinning of the oil at high temperatures, ensuring its stability, controls the deposits and sediments of varnish, rust and carbon.

APPLICATION

- diesel engines for heavy machinery, agricultural construction equipment, hydraulic lifting systems, subjected to heavy operation, without particle filter (DPF);
- unless otherwise recommended in the machine manual, the maximum interval between two oil changes will be maximum 30.000 Km or a year.

PROPERTIES

Viscosity grade SAE	10W40
API Service	CI-4/SL
Density at 15°C [kg/m³], max	880
Kinematic Viscosity at 100°C [mm²/s]	12.5 - 16.3
Viscosity Index, min	150
Flash Point [°C], min	215
Pour Point [°C], max	-30

PACKAGING

0.4kg	1kg	4kg		180kg		
0.231	0.45l	0.5I	0.6l	0.91	1l	□ 3I
<u>4</u> I	∑ 5I			⊠ 60I	∑ 208I	X 1000l

HEXOL